

REVISIONS TO SPECIFICATION

Page 4, line 8:

The object of the invention is achieved by ~~the characteristics in claim 1~~ a lamp, wherein at least the outer layer and/or at least one inner layer of the interference filter (3) comprises a protective layer (4) to reduce thermal and/or intrinsic stresses, and wherein the thickness of the protective layer (4) or protective layers (4) has a value below 40% of the value of all other layers with the lower refractive index.

Page 5, line 8:

One ~~The preferred~~ embodiment ~~according to claim 3~~ requires that the layer of the interference filter with the lower refractive index preferably comprises SiO_2 and that the second layer of the interference filter comprises a material which has a higher refractive index than SiO_2 , preferably mainly zirconium oxide (ZrO_2).

Page 5, line 12:

~~The preferred~~ One embodiment ~~in claim 4~~ requires that the second layer comprises a material from the group of titanium oxide, tantalum oxide, niobium oxide, hafnium oxide, silicon nitride, particularly preferably zirconium oxide ZrO_2 , or a mixture of these materials. ZrO_2 is particularly preferred as it absorbs less and is more temperature-resistant than most other materials.

REVISIONS TO SPECIFICATION

Page 5, line 29

The object of the present invention is also achieved by an illumination unit with at least
| one lamp according to any one of the claims ~~1 to 6~~.